



Service-Information



BMW MOTORRAD GMBH Service R-VK-10 wb/ur	Motorcycle R50/5-R100RS Technic Wheels & Tires	Munich, May 77 36 003 77(1036R)
---	--	------------------------------------

For U.S.A. and Canada only

Subject: Tire Pressures and Minimum Tread Depth

Dear Dealer,

Tire Pressures:

The following tire pressures are the approved, tested correct pressures on standard equipped tires and tubes.

Front Wheel:

		<u>Solo</u>	<u>Permissible Gross Weight</u>
Metzeler	3.25 x 19 - S or H, Rille 12	27 psi	30 psi
Conti	3.25 x 19 - S or H, RB, RB2	27 psi	30 psi

Rear Wheel:

Metzeler	4.00 x 18 - S or H, C6 or C66	25 psi	30 psi
Conti	4.00 x 18 - S or H, K111, K112 or K112A	25 psi	30 psi

Above pressures are recommended up to 100 MPH.

Over 100 MPH, add 3 psi to each tire pressure.

Solo never exceeds 30 psi.

The above recommendation is for "cold" tires.

Tread Depths:

A. Legal, minimum depth = 1 mm (0.040")

B. Recommended, up to 80 MPH = 2 mm (0.080")
over 80 MPH = 3 mm (0.120")

Yours truly,

BMW MOTORRAD GMBH, Munich

Manus
González Blank