

Service-Information



| | | |
|--------------------|------------------|----------------------------------|
| Group 11 Engine | February 1980 | Bulletin No.: 11 013 80(2013) |
|--------------------|------------------|----------------------------------|

- For U.S.A. and Canada Only -

Subject: Valve Clearances on R 65 - R 100 RT

The following are correct valve clearances, updated, to give the best possible performance:

| | |
|-------------|--|
| <u>R 65</u> | |
| Inlet: | - 1000 km (600 miles) = 0.15 mm (.006") + 1000 km (600 miles) = 0.10 mm (.004") |
| Exhaust: | - 1000 km (600 miles) = 0.25 mm (.010") + 1000 km (600 miles) = 0.15 mm (.006") |

*See
Reader's
Manual
for year
model*

| | |
|--------------------------|--|
| <u>R 80/7 - R 100 RT</u> | |
| Inlet: | - 1000 km (600 miles) = 0.15 mm (.006") + 1000 km (600 miles) = 0.10 mm (.004") |
| Exhaust: | - 1000 km (600 miles) = 0.20 mm (.008") + 1000 km (600 miles) = 0.15 mm (.006") |

NOTE: Always adjust valves with engine cold (approx. 20°C-68°F)

BMW MOTORRAD GMBH
After-Sales Service
Munich